



Features:

1. Fully enclosed design, the whole monitor is dustproof.
2. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
4. Adopt 5 wire resistive touch panel, stable, durable, anti-interference.
5. High performance mainboard, 7x24 continuous operation.
6. VGA+HDMI+DVI interfaces, USB for touch.
7. 12-36V wide voltage support.
8. Anti-interference.
9. Ultra-thin front bezel 3mm, ideal for embedded mounting.

LCD panel

Panel size	10.1"
Resolution	1280*800
Aspect ratio	16:10
Support Color	16.7M colors
Brightness (cd/m ²)	300+
Contrast ratio	600:1
View angle	85°/85°/85°/85° (R/L/U/D)

Touch panel

Touchscreen Type	5 wire resistive touch
Surface Hardness	3H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>35 million times

Signal Ports

VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI
Audio in/out	Optional

OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.

Power Supply

External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V-36V
Power consumption	≤9W

Enclosure

Material	Aluminum Alloy
Color	Black, Silver
VESA mounting	75×75mm/100×100mm
IP grade	Front panel IP65 waterproof

Operating Environment

Temperature Range	Operating: -10 to 60°C, Storage: -20 to 70°C
Relative humidity	Operating: 10% to 80%, Storage: 5% to 90%

Packing Details

Net weight	2.1kg
Gross weight	3.6kg
Product Dimension	29.36*19.36*5.35cm
Packing size	40*35*16cm
Accessories	Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card

Other

Mounting	Embedded mounting screws
	Wall mounting brackets (Optional)
	Desk stand holder (Optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS

10.1" Touch Monitor 1280*800

