



**Features:**

1. Fully enclosed design, the whole monitor is dustproof.
2. Front bezel aluminum alloy brushed metal craft, seamless design, front panel IP65 waterproof.
3. Aluminum alloy shell, good mechanical properties, excellent heat dissipation.
4. Adopt multi-points PCAP touch panel, high sensitive and fast-response. Covered with 2mm tempered glass for vandalproof.
5. High performance mainboard, 7x24 continuous operation.
6. VGA+HDMI+DVI interfaces, USB for touch.
7. 12-36V wide voltage support.
8. Anti-interference.
9. Ultra-thin front bezel 3mm, ideal for embedded mounting.

**LCD panel**

Panel size	13.3"
Resolution	1920*1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m <sup>2</sup> )	300+
Contrast ratio	800:1
View angle	85°/85°/85°/85° (R/L/U/D)

**Touch panel**

Touchscreen Type	Project Capacitive Touch (10 points )
Surface Hardness	7H
Luminousness	90%
Touch Interface	USB (RS232 optional)
Touch response time	2ms
Working Life	>50 million times
Touch options	(5 wires restive touch optional)

**Signal Ports**

VGA	1x VGA
DVI	1x DVI
HDMI	1x HDMI
Audio in/out	Optional

## OSD

OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select, etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese, etc.
Support OS	Windows XP, Windows /7/8/10, Linux, Mac OS X, Android, ect.

## Power Supply

External Power Supply	AC 100 - 240V, 50-60Hz
Working voltage	DC 12V-36V
Power consumption	≤35W

## Enclosure

Material	Aluminum Alloy
Color	Black, Silver
VESA mounting	75x75mm/100x100mm
IP grade	Front panel IP65 waterproof

## Operating Environment

Temperature Range	Operating: -10 to 60°C, storage: -20 to 70°C
Relative humidity	Operating: 10% to 80%, storage: 5% to 90%

## Packing Details

Net weight	4kg
Gross weight	5kg
Product Dimension	37.36*24.52*5.7cm
Packing size	44*39*21cm
Accessories	Power adapter, VGA cable, USB touch cable, embedded screws, user manual, warranty card

## Other

Mounting	Embedded mounting screws
	Wall mounting brackets (optional)
	Desk stand holder (optional)
Warranty	1 year warranty
Certificates	CE, FCC, RoHS

